



## 26-INCH LCD MONITOR

- 1366 x 768 Resolution
- Bright 500 cd/m<sup>2</sup> Display
- HDMI, VGA Inputs
- 3D Comb Filter with De-Interlace
- 2x Looped BNC Inputs
- VESA Compliant Hole Pattern
- Unit accepts 3-prong 110 VAC Cable at the Monitor. No external power adapter required.

## S P E C I F I C A T I O N S

26-inch CCTV LCD Monitor		Part Number - SM26M-B
<b>Display</b>	Screen Size	26"
	Aspect Ratio	16:9
	Resolution	1366 x 768
	Brightness (cd/m <sup>2</sup> )	500
	Response Time	8 ms
	Viewing Angle (H/V)	170° / 170°
	Contrast Ratio	1000:1
	Pixel Pitch	0.1405 x 0.4215mm
<b>Video Inputs</b>	Digital Inputs	HDMI, VGA
	Composite Inputs / Outputs (BNC)	2 / 2
<b>Audio</b>	Audio Input	1/8" Phono Jack
	Audio Output(s)	2 x RCA Out (L/R)
<b>Power</b>	Power Consumption	< 130W
<b>Design Features</b>	Features - Signal Filter	3D-Comb, De-Interlace
	Features - PIP - I composite, I digital	Yes
	Wall Mount Hole Pattern	200 x 100mm
	Remote	Included
	Power Supply	N/A, unit accepts 110VAC
	Connector Location / Secured	Side / Yes
<b>Standards</b>	Approvals	CE, FCC, RoHS
<b>Dimensions</b>	Dimensions w/o stand (H/W/D)	25.2 x 15 x 3.55 in (640.8 x 381 x 90.2 mm)
<b>Weight</b>	Monitor Weight	25.4 lbs (11.5kg)